



KOMPATTO SC 5030

TECHNICAL DATA

ENGINE ISUZU

-Power	kW/Hp	32/43,5
-Consumption	L/h	8,5

VIBRATING LOADING HOPPER

- Grid dimensions	mm.	2500x1000
- Screening grid	No.	02

FEDDING BELT

- Length	mm.	2500
- Width	mm.	800
- Hopper capacity	m ³	2,5
- Loading height	mm.	2600

FINE MATERIAL BELT

- Length	mm.	6300
- Width	mm.	600
- Pile height	mm.	2800

MEDIUM MATERIAL BELT

- Length	mm.	6300
- Width	mm.	600
- Pile height	mm.	2800

OVERSIZE MATERIAL BELT**

- Length	mm.	3700
- Width	mm.	800
- Pile height	mm.	2150
- 2°Pile height**	mm.	2450

CRAWLED TRACK WITH PADS

- Length	mm.	2750
- Width	mm.	400

*PERFORMANCE

- Production	T/h	50-350
- Max size	mm.	600
- Standard weight	Kg.	12000

STANDARD MACHINE

- Remote control for undercarriage movements
- Screening grid a bars

ACCESSORIES

- Remote control for all movements
- Dust dumping system
- Screening grid made in metal sheet
- Screening grid made metallic net

DIMENSIONS At Work Transport

- Length mm.	9860	9860
- Width mm.	10780	2250
- Height mm.	2400	2500

**The screen production performance depends by the type of material.*

**When needed can be used for just 2 selections lowering the oversize belt.*



The technical data and specifications hereby supplied are merely indicative. Komplet reserves the right to modify them without notice.

Dealer:

KOMPLET
RECYCLING SYSTEM

www.komplet.it info@komplet.it

+39 071 66 09 823 +39 071 66 11 069